

# A Fusion Development Facility to Test Divertor and PFC Solutions for DEMO

A.W. Leonard, A.M. Garofalo, R.D. Stambaugh, P.C. Stangeby, C.P.C. Wong and V.S. Chan

Presented at the ReNew Theme III workshop; Taming the Plasma Material Interface  
UCLA, March 4-6, 2009

# Significant Gaps from ITER to DEMO for PFC Solutions

- **Erosion and material migration**
  - Higher power density and higher duty cycle
  - More aggressive heat flux control required
  - Tons of PFC material will be eroded and redeposited
- **Tritium fuel cycle**
  - DEMO must breed its own tritium
  - Only small fraction of injected tritium fuel can remain in device
- **High temperature**
  - Blanket temperature  $\geq 600$  °C required for efficient electricity generation
  - PFC characteristics fundamentally change at high temperature
- **Off normal events**
  - Disruptions must be eliminated, or substantially mitigated
  - ELMs must be essentially eliminated


# A RESEARCH Facility for PFC Development is Needed to Bridge the Gaps to DEMO

## A PFC research facility should encompass:

- **Tritium breeding**
  - PFC issues are central to obtaining TBR >1; Thin PFCs for neutron flux to blankets, tritium retention and permeation in PFCs
- **High power density and duty cycle**
  - Tests of heat flux control solutions compatible with high core confinement
  - Test designs to handle large levels of gross and net erosion and redeposition
  - Develop diagnostics for monitoring PFC erosion and integrity
- **High temperature**
  - Tritium retention and permeation change drastically at high temperature
  - PFC surface properties, reworked by the plasma and neutron, may change at high temperature
- **High neutron fluence**
  - Capability to test PFC designs, material and surface properties to > 20 dpa
- **Flexibility**
  - Ability to change out and test alternative PFC materials and designs

# FDF is an research facility to address the PFC gaps to DEMO

- **Compact**
  - Utilize AT physics for a high power density device at modest size,  $\sim 1.3 \times$  DIII-D
- **Helium cooled PFCs**
  - Optimize vessel and PFC temperatures
  - Other options possible
- **Steady state**
  - 2 week discharges, 30% duty cycle over a year
- **High density**
  - Enhanced radiative dissipation
- **Flexibility with removable TF**
  - PFCs assembled outside vessel
  - Divertor and other PFCs can be changed in timely manner



# FDF Can Conduct a Broad and Flexible Research Program

- **Test a variety of PFC materials**
  - Possible carbon PFCs for initial operation and discharge optimization; Oxygen bake for periodic cleanup
  - All potential materials can be installed and tested W, Mo, RAFM, engineered BW, flow through C
  - Large volume of PFC material will be eroded and redeposited with unknown characteristics
  - Complete surface inspection, and possible replacement at regular intervals
- **A number of PFC designs can be tested**
  - Swirl tubes and hypervaportrons for heat removal
  - Joining of PFCs to heat sink; Brazing, mechanical clamping, etc.
- **Heat flux solutions**
  - High density for radiative heat flux dissipation
  - Compatibility of radiative divertors with optimized core confinement
  - Precision divertor alignment to maximize use of flux expansion
  - Innovative divertor configurations for increased flux expansion; Super-X


# FDF Research Capability (cont.)

- **Tritium retention**

- Tritium retention decreases significantly at higher temperature
- Tritium diffusion, permeation, in high Z metals increases at high temperature
- Surface properties at high temperature may limit flux of tritium into bulk
- Optimal operating temperature for tritium control very uncertain


- **Tritium breeding**

- Credible PFC designs for net tritium breeding can be tested



# FDF Research Capability (cont.)

- **Component lifetime tests**
  - 20-40 dpa in a 5 year operating period can test material integrity of PFC materials
  - Effects of neutrons on eroded and redeposited PFC material can be examined
- **RAMI**
  - High duty cycle over years required high reliability and availability
  - Maintenance techniques can be developed
  - Diagnostics important for evaluating erosion, tritium retention and PFC integrity



# Staged Schedule for Experimental Approach

- **Startup phase; 4 years**
  - Shorter pulses for system checkout
  - Optimize performance with PFCs forgiving to off normal events
- **1<sup>st</sup> experimental phase; 5 years, 12 dpa**
  - Begin steady state operation
  - Conservative PFC and blanket design for initial evaluation
- **Maintenance; 2 years**
  - Install DEMO relevant PFC, divertor and blanket systems
- **2<sup>nd</sup> operation phase; 5 years, 25 dpa**
  - Test performance of DEMO relevant PFC designs
- **Maintenance; 2 years**
  - Install optimized PFC designs
- **3<sup>rd</sup> operation phase; 5 years, 40 dpa**
  - Final testing of PFC, divertor and blanket designs for DEMO

# A Staged Research Plan for Increasingly Optimized Operation

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
	← START UP → H D DT				FIRST MAIN BLANKET						SECOND MAIN BLANKET						THIRD MAIN BLANKET							
Fusion Power (MW)	0	0	125	125	250						250						250					400		
$P_N/A_{WALL}$ (MW/m <sup>2</sup> )				1	1				2		2						2					3.2		
Pulse Length (Min)	1	10		SS					SS		SS						SS					SS		
Duty Factor	0.01	0.04		0.1	0.2					0.2					0.3		0.3					0.3		
T Burned/Year (kG)	0.28			0.7	2.8					2.8					4.2		4.2					5		
Net Produced/Year (kG)					-0.14					0.56		0.56					0.84		0.84					1
Main Blanket	He Cooled Solid Breeder Ferritic Steel										Dual Coolant Pb-Li Ferritic Steel						Best of TBMs RAFS?							
TBR				0.8	1.2					1.2					1.2		1.2					1.2		
Test Blankets				1,2						3,4   5,6						7,8   9,10								
Accumulated Fluence (MW-yr/m <sup>2</sup> )	0.06			1.2						3.7						7.6								